

# PARTS WASHERS

### **MODEL 960-970**



# DRAWER STYLE HIGH PRESSURE/LOW VOLUME PERFORMANCE

The Model 960 is a high pressure, low volume washer which utilizes a drawer type construction which allows for cleaning large, heavy and bulky parts. In addition, large baskets of parts will fit in this washer.

The door is attached to a carriage which moves in and out of the cabinet. The rotating turntable is mounted on the carriage with the drive being mounted on the door. The standard weight capacity of 3000 pounds is easily increased because of the structure of this washer. When open, clearance over the turntable is open for fork truck loading or overhead loading with hoists or cranes.

The operator holds a push button while the door closes and the cleaning cycle is automatically started. At the end of the cycle the door opens, letting the operators know that the cycle is completed. With the size of this washer, a minimum of 10 HP pump is used providing 18 GPM at 700 PSI. For cleaning requirements requiring additional volume a 20 HP pump is available.

Construction of this washer is for heavy duty and continuous opertions and utilizes 304 stainless steel for the spray chamber and reservoir tank.

There are a variety of options available for the washer, including drying, rinsing, oil skimming and electronic controls. By choosing the proper option, you can tailor the washer for your requirements.

Biodegradable detergents and hot water are the cleaning solution used, which provide a safe and environmentally friendly solution. ADF detergents include rust inhibitor for steel parts and are safe on other materials such as brass, aluminum, stainless steel, copper, rubber, plastic or glass.

Filtration of the wash solution is standard with this model, including a primary 100 micron felt blanket filter and secondary cartridge system. With rating of 3, 5, 10, 25 and 50 micron, the customer can choose the proper cartridge for his requirements.

## ADF SYSTEMS, LTD.

1302 19TH ST. N. P.O. BOX 278 HUMBOLDT, IOWA 50548 USA

TELEPHONE: 800-959-1191 FAX: 800-798-5100 TELEPHONE: 515-332-5400 FAX: 515-332-4475

WEB SITE: www.adfsys.com

#### **DISTRIBUTED BY:**

#### MODEL 960 DRAWER TYPE PARTS WASHER HIGH PRESSURE, LOW VOLUME TECHNICAL DATA

PART NUMBER	DESCRIPTION	MACHINE AMPERAGE	GPM - PSI
	32" diameter turntable, 36" working height, 7.5 KW heater, 37 gallon tank		
9634-032-036	Model 960, 10HP, 230V/60HZ/3PH	50	18 GPM, 700 PSI
9644-032-036	Model 960, 10HP, 460V/60HZ/3PH	24	18 GPM, 700 PSI
9734-032-036	. Model 970, 20HP, 230V/60HZ/3PH	76	36 GPM, 700 PSI
9744-032-036	Model 970, 20HP, 460V/60HZ/3PH	40	36 GPM, 700 PSI
	42" diameter turntable, 36" working height, 7.5 KW heater,	56 gallon tank	
9634-042-036	Model 960, 10HP, 230V/60HZ/3PH	50	18 GPM, 700 PSI
9644-042-036	Model 960, 10HP, 460V/60HZ/3PH	24	18 GPM, 700 PSI
9734-042-036	Model 970, 20HP, 230V/60HZ/3PH	76	36 GPM, 700 PSI
9744-042-036	Model 970, 20HP, 460V/60HZ/3PH	40	36 GPM, 700 PSI

NOTE: 1. For machines with rinse to drain feature, add suffix "R" to part number.

2. Low water level switch for heater protection, standard.

3. Fused disconnect, optional.

PUMP 3 Cylinder Axial Diaphragm Type		ONTROLS All 115V Fused	
TIMER Electronic Timer with Push Button Start-Stop		EMPERATURE 160 Degree F.	
HEATER Electric SS Plug, Incaloy Elements TEMP. CONTROL Thermostat control in Emmersion Heater Box		Convenient terminal block in	
	CONNECTION	electrical box	
Secondary: High pressure cartridge type	ENCLOSURE	NEMA 12	
10 HP (2) Cartridges; 20 HP (4) Cartridges	BASKET	None furnished	
ISTRUCTION: RAY CHAMBER 304 Stainless steel		Mounted on subframe base	
	TURNTABLE ROTATION LOAD CAPACITY	1-1/2 RPM 3000 lbs.	
Brass, Mallable or Plated	QTY OF NOZZLES	32" 10 HP-20 42" 10 HP-20 32" 20 HP-40 42" 20 HP-40	
Carbon Steel	DOOR	Electric Power Operated	
Carbon Steel	WEIGHT	32" 10 HP 3100#3100#	
NE 32" 36" Part Height - 118" x 72" x 102"  SIONS**  42" 36" Part Height - 138" x 82" x 102"		32" 20 HP     3500#3500#       42" 10 HP     3600#3600#       42" 20 HP     4100#4100#	
	Electronic Timer with Push Button Start-Stop Electric SS Plug, Incaloy Elements Thermostat control in Emmersion Heater Box Primary: Filter tray-100 micron felt filter Secondary: High pressure cartridge type 10 HP (2) Cartridges; 20 HP (4) Cartridges  304 Stainless steel  Carbon Steel Brass, Mallable or Plated Stainless Steel Nozzles Carbon Steel Carbon Steel Carbon Steel Carbon Steel	Electronic Timer with Push Button Start-Stop Electric SS Plug, Incaloy Elements Thermostat control in Emmersion Heater Box Primary: Filter tray-100 micron felt filter Secondary: High pressure cartridge type 10 HP (2) Cartridges; 20 HP (4) Cartridges  304 Stainless steel  Carbon Steel Brass, Mallable or Plated Stainless Steel Nozzles Carbon Steel Carbon Sfeel  32" 36" Part Height - 118" x 72" x 102"  MAX. TEMPERATURE  ELECTRICAL CONNECTION ENCLOSURE  BASKET  STATIONARY  TURNTABLE ROTATION LOAD CAPACITY  QTY OF NOZZLES  DOOR WEIGHT (NET/SHIPPING)	

NOTE: Consult your distributor or the factory for available options and accessories.

Prices and specifications subject to change without notice - all prices \$USD and F.O.B. Humboldt, Iowa, U.S.A. This equipment will be constructed in accordance with the above specifications, and in accordance with ADF equipment standards at the time of manufacture. No other conditions, specifications, or components will be included unless expressly agreed to in writing by ADF Systems, Ltd. There are no implied warranties or conditions. No verbal agreements will be accepted as part of any purchase order for equipment. Further documentation or services will be at additional cost to the buyer.

<sup>\*\*</sup> All dimensions are for base machine. Manufacturer reserves the right to make engineering changes, which may change dimensions.

Additions of accessories and/or customer requested changes might also change dimensions. Consult your distributor or the factory for a footprint