

COLD water pressure washers

- Several cold water models to choose from, with pressures ranging from 1000 to 4000 PSI.
- Available in electric motor and gasoline driven models.
- Industrial grade pumps and motors.
- Trigger shut-off gun on all models.
- Higher performance available on built-to-order basis.



Downdraft tables

available in standard sizes
ranging from
24" x 30" to 36" x 96"
CUSTOM SIZES AVAILABLE



We also manufacture a full line of

parts washers

to meet virtually every cleaning
application.



ADFS[®]
SYSTEMS, LTD

**PRESSURE
WASHERS**

1302 19th St. North • P.O. BOX 278
HUMBOLDT, IOWA 50548-0278 USA
Phone: 800-959-1191 Fax: 800-798-5100
Phone: 515-332-5400 Fax: 515-332-4475
Visit our web site: www.adfsys.com

HOT water series



M1000/M1200
Portable, Oil-Fired Models



M1400/M1500/M2100
Portable, Oil-Fired Models



M3000/M3500
Portable, Oil-Fired Models



M2000/M2200/M2300
Portable, Oil-Fired Models
W/Hose Reel Kit Option



M1000/M1300/M1500
M2000/M2100/M2200
M2300/M3000/M3500
Stationary, Gas-Heated
Models

Other ADF available Styles & Models

Contact ADF for more information



HOT WATER HEATER
Available in Oil or
Gas-Fired Models



ALL ELECTRIC HEATED
Available in Models
Ranging up to
4GPM@3000PSI
230V/460V/3PH only



M2100/M2000
/M3000/M3500
Stationary, Gas Engine,
Oil-Fired



M2100/M2000
M3000/M3500
Portable,
Gas Engine,
Oil-Fired



Open Style,
Gas-Heated Model



M2100/M2000
Portable, Gas Engine,
Oil-Fired



GENERAL SPECIFICATIONS	1000	1200	1300	1400	1500	2000	2100	2200	2300	3000	3500
Available Capacity's	2.1 gpm / 3gpm	3 gpm	4gpm	2.2 gpm / 3 gpm	3 gpm	4 gpm	3.5 gpm	3.6 gpm	4.2 gpm	4.0 gpm	5 gpm
Available Pressures	1000 / 700	1000	1200	1250 / 1000	1500	2000	2100	2500	1800	3000	3000
Pump Type	All pumps are Positive Displacement with ceramic plungers and oil bath crankcase										
Pump Motor	1-1/2 HP	2 HP	3 HP	2 HP	3 HP	5 HP	5 HP	6 HP	6 HP	7-1/2 HP	10 HP
Coil	1/2" ID A53 Sch 80 Pipe Vertically Fired										
*Oil Fired Burner Models	U/L Approved, Oil Fired, Forced Air Burner w/ Automatic Ignition, 1/8 HP Burner Motor w/ thermal overload protection and a High Capacity oil/water separator Fuel Filter										
Gas Fired Burner Models	Ring Type Aspirating Jet Gas Fired Burner w/ Natural Draft - All controls AGA approved - Available in Natural Gas or L.P. Gas										
Temperature Control	Adjustable to 210 degs. F										
Flow Switch	Automatically shuts down burner when water flow has stopped										
Unloader Valve	Provides pressure relief for pump when trigger gun is closed										
Trigger Gun	Trigger shut off with insulated handle										
Wand	35" (88.9 CM) with insulated grip, extra extensions optional										
Hose	3/8 (9.5 MM) x 50 ft. (15.25 M) wire braided; 12,000 PSI (843.6 KG/CM) burst rating, extra lengths optional										
Nozzle	Sprayflex nozzle adjustment 0 through 80 degs.										
Float Tank	304 Stainless Steel										
Portability	Oil Fired Models Standard on (4) pneumatic wheels - Gas Fired Models Stationary										

*All Fuel Tanks are removable, non-contaminating high density polyethylene - M1000 & M1200 have a 5 gallon Fuel tank, all other models are 12 gallon
Oil Fired Burners will fire on Kerosene, #1 Home Heating Oil or #2 Diesel Fuel

ADF detergents

ADF has a large selection of highly concentrated, biodegradable detergents.

